Searching PAJ Page 1 of 2

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-275016

(43) Date of publication of application: 08.10.1999

(51)Int.Cl. H04B 10/08

H04B 3/46 H04J 14/00 H04J 14/02

(21)Application number: 11-028031 (71)Applicant: LUCENT TECHNOL INC

(22)Date of filing: 05.02.1999 (72)Inventor: JENNINGS MARK R

LEONE FRANK SALVATORE
PIMPINELLA RICHARD JOSEPH

(30)Priority


Priority number: 98 19213 Priority date: 05.02.1998 Priority country: US

## (54) SYSTEM AND METHOD FOR MONITORING OPTICAL LINK AND FOR SPECIFYING STATE OF THE LINK

## (57)Abstract:

PROBLEM TO BE SOLVED: To specify or detect the soundness of an optical link by allowing a 2nd device to monitor the optical link, based on the received optical signal having the first wavelength and then detect the state of the optical link.

SOLUTION: An optical signal having wavelength  $\lambda 1$  is produced by a laser site source 120 and supplied to one of inputs of a WDM 124. Another optical signal having wavelength  $\lambda 2$  is received from a transmitter 102 and supplied to the other input of the WDM 124. Both optical signals of  $\lambda 1$  and  $\lambda 2$  are transmitted to an optical link 106 via the WDM 124. A transmitter 114 produces an optical signal having wavelength  $\lambda 3$ , which is supplied to one of inputs of a WDM 130. The optical signals of  $\lambda 1$  and  $\lambda 3$ 



are transmitted to a central station via the WDM 130 and then to a system optical link 108. In